

KLINE

GENERAL SPECIFICATIONS

Width	54"
Weight	17 oz/linear yard
Composition	91% Polyester 7% Polyurethane 2% Silicone
Backing	Polyurethane
Minimum Yardage	500 Yards
Custom Color	

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
UFAC Class 1	Passes
NFPA 260	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 4.5
Seam Slippage	Fill: 46 Warp: 46.5
Tensile Strength	Fill: 195 Warp: 225
Tear Strength: Tongue Tear	Fill: 44.4 Warp: 46.0
Colorfastness to Light	Class 5 at 40 Hours
Brush Pill	Class 4

RECOMMENDED APPLICATIONS



WORKSPACE



HEALTHCARE



HOSPITALITY



RESTAURANT



SENIOR LIVING

GENERAL TREATMENTS

Moisture Resistant	Yes
Bleach Resistant	Yes- 10% Dilution
Stain Resistant	Yes
Cleaning Code	SW - Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned. BC - Lightly spray with a 10% dilution of household bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

REDUCED ENVIRONMENTAL IMPACT

- No added flame retardant chemicals
- No added anti-bacterial/ anti-microbial chemicals
- Lead/ Heavy metal free
- BPA free/ Tris free/ Formaldehyde free
- Does not contain conflict minerals
- *Prop 65 Compliant
- *AB2998 Compliant

FINISHES



*ACT® Registered Certification Marks