



# HEYWARD

## GENERAL SPECIFICATIONS

Width	54"
Weight	16.6 oz/linear yard
Composition	100% Polyester
Backing	SBR
Minimum Yardage	500 Yards
Custom Color	

## FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

## CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.

## FINISHES



## PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 4.5 Dry: 4.5
Seam Slippage	Fill: 55 Warp: 83.5
Tensile Strength	Fill: 45 Warp: 275
Tear Strength: Tongue Tear	Fill: 19.8 Warp: 25.4
Colorfastness to Light	Class 3.5 at 40 Hours
Brush Pill	Class 4.5
Stain Resistant	Resilience TX
Cleaning Code	SW

## RECOMMENDED APPLICATIONS



\*ACT® Registered Certification Marks