



MUSE

GENERAL SPECIFICATIONS

| | |
|-----------------------|-------------------|
| Width | 54" |
| Weight | 32 oz/linear yard |
| Surface Composition | 100% PVC |
| Substrate Composition | 100% Polyester |
| Gauge | 0.048 |
| Thickness | 1.15 mm |

FLAME RETARDANCY SPECIFICATIONS

| | |
|-----------------|--------|
| CAL-TB 117-2013 | Passes |
| NFPA 260 | Passes |
| UFAC Class 1 | Passes |

REDUCED ENVIRONMENTAL IMPACT

- No added Flame Retardant Chemicals
- No added Anti-Microbial/Anti-Bacterial Chemicals
- Phthalate Free
- Lead/Heavy Metal
- BPA Free/TRIS Free/Formaldehyde Free
- Does not contain Conflict Minerals
- CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

| | |
|----------------------------|------------------------|
| Abrasion | 500,000+ DR |
| Colorfastness to Crocking | Wet: 5 Dry: 5 |
| Seam Slippage | Fill: 40 Warp: 60 |
| Tensile Strength | Fill: 95 Warp: 131 |
| Tear Strength: Tongue Tear | Fill: 6.5 Warp: 8.5 |
| Stain Resistant | Passes |
| Cold Crack | -20° |
| Colorfastness to Light | 500 Hours |
| Bleach Resistant | Yes - 10% Dilution |

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

