



PATHFINDER

GENERAL SPECIFICATIONS

Width	54"
Weight	30 oz/linear yard
Surface Composition	100% PVC (Phthalate Free)
Substrate Composition	100% Polyester Brushed Knit
Gauge	0.048
Thickness	1.20 mm
Substrate Weight	4.4 oz

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

REDUCED ENVIRONMENTAL IMPACT

- Phthalate Free
- Lead Free
- BPA Free/TRIS Free/Formaldehyde Free
- Does not contain Conflict Minerals
- CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	250,000 DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 43 Warp: 54.3
Tensile Strength	Fill: 92 Warp: 105
Tear Strength: Tongue Tear	Fill: 7.5 Warp: 6.4
Colorfastness to Light	200 Hours
Cold Crack	-20°
Coating Adhesion	Fill: 6.3 Warp: 6.3
Flex Testing of Finish	25,000 Cycles
Bleach Resistant	Yes
Stain Resistant	Yes

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

