



ANTHEIA

GENERAL SPECIFICATIONS

Width	54"
Weight	31 oz / linear yard
Composition	Surface: 100% Hyphyn™ Biodegradable PVC Backing: 100% Hyphyn™ Biodegradable Polyester
Finish	Resilience™ Protection

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	250,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Coated Adhesion	Fill: 5.03 Warp: 4.11
Breaking Strength	Fill: 71.5 Warp: 88.5
Seam Strength	Fill: 45.4 Warp: 46.8
Tear Strength	Fill: 12.6 Warp: 9.6
Colorfastness to Light	300 Hours
Cleaning Code	SW, BC
Bleach Cleanable	Yes - 10% Dilution

SUSTAINABILITY SPECIFICATIONS

Biodegradation (in landfill)	90%+ Degradation / 24 Months
VOC Emissions	Low VOC - CDPH Sec. 01350

RECOMMENDED APPLICATIONS



HOSPITALITY



RESTAURANT



WORKSPACE



SENIOR LIVING



HEALTHCARE



CLEANING INSTRUCTIONS

Clean the soiled area with 10% solution of household bleach and water. Apply the mixture with a soft cloth or sponge, then wipe the surface thoroughly. It is important to rinse the cleaned area with fresh water after applying the bleach solution and dry with a soft towel.

REDUCED ENVIRONMENTAL IMPACT

Will biodegrade over 90% in a landfill environment within 2 years per ASTM D5511

Low VOC

No detectable chemicals of concern in post-degradation soil per ASTM E1963

No negative effect on post-degradation soil

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals - AB2998 compliant

No added anti-bacterial / anti-microbial chemicals

Phthalate free / PFAS-free

Lead / heavy metal free

BPA free / tris free / formaldehyde free

Does not contain conflict minerals

*Prop 65 Compliant

*CAB2998 Compliant



*ACT® Registered Certification Marks



KEYSTONBROS.COM | KBCONTRACT.COM

05/2025