

BEAUMONT

GENERAL SPECIFICATIONS

Width	54"
Weight	31.7 oz / linear yard
Composition	Surface: 100% PVC Backing: 100% Polyester
Finish	Resilience™ Stain Resistance

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
MVSS302	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	250,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Coated Adhesion	Fill: 5.4 Warp: 6.8
Breaking Strength	Fill: 146 Warp: 146
Seam Strength	Fill: 69.1 Warp: 59.6
Tear Strength	Fill: 17 Warp: 11.5
Colorfastness to Light	300 Hours
Bleach Cleanable	Yes - 10% Dilution

CLEANING INSTRUCTIONS

Prompt cleaning is always recommended. Ordinary dirt and stains can be removed with a mild soap and water. Rinse the cleaned area with clean water and dry with a lint-free cloth. Beaumont will resist, without serious discoloration, the repeated actions of normal dilutions of detergent and solvent based cleaners.

Bleach Instructions: Clean the soiled area with 10% solution of household bleach and water. Apply the mixture with a soft cloth or sponge, then wipe the surface thoroughly. It is important to rinse the cleaned area with fresh water after applying the bleach solution and dry with a soft towel.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead / Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

PFAS Free

*Prop 65 Compliant

*CAB2998 Compliant

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

