



BEEKMAN VELVET

GENERAL SPECIFICATIONS

Width 54"

FLAME RETARDANCY SPECIFICATIONS

18.1 oz / linear yard Weight

Composition 100% Polyester

> Finish Resilience TX

> > Passes

Passes

Passes

Minimum Yardage 300 yards

Custom Color

CAL-TB 117-2013

NFPA 260

UFAC Class 1

dry cleaned.

This product does not pose any exposure risks associated with the chemicals in Prop 65

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning

Cushion covers should not be removed and

REDUCED ENVIRONMENTAL IMPACT

solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance.

Lead / Heavy Metal Free

CLEANING INSTRUCTIONS

AB 2998 Compliant - Free of Flame Retardant Chemicals

PFAS/PFC Free Stain Resistance

HPD Available

REACH Compliant

RoHs Compliant

PERFORMANCE SPECIFICATIONS

Abrasion 100.000 DR

Colorfastness Wet: 4.5 to Crocking Dry: 5

Seam Slippage Fill: 71.4

Warp: 77.4

Tensile Strength Fill: 259 Warp: 308

> Colorfastness Class 4.5 at 40 Hours

> > to Light

Cleaning Code S/SW

Stain Resistant Yes

> Brush Pill Class 5

RECOMMENDED APPLICATIONS









HOSPITALITY RESTAURANT WORKSPACE SENIOR LIVING



*ACT® Registered Certification Marks

FINISHES

