



CHANNEL

GENERAL SPECIFICATIONS

Width	54"
Weight	15.60 oz / linear yard
Composition	100% Polyester
Railroaded	Yes
Repeat	13.5" H x 21.43" V
Finish	Crypton® Stain & Moisture Barrier

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion (Wyzenbeek)	100,000 DR
Colorfastness to Crocking	Wet: 4.5 Dry: 4.5
Seam Slippage	Fill: 49.1 Warp: 59.9
Break Strength	Fill: 32.1 Warp: 90
Colorfastness to Light	Class 4 at 40 hours
Cleaning Code	WS, BC
Brush Pill	Class 3
Bleach Cleanable	Yes

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned. BC - Lightly spray with a 10% dilution of household bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65.

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead / Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

PFAS Free

*Prop 65 Compliant *CAB2998 Compliant

RECOMMENDED APPLICATIONS





