



CIRCUIT

GENERAL SPECIFICATIONS

Width	54"
Weight	30 oz / linear yard
Composition	Surface: 100% PVC Backing: 100% Polyester
Finish	PFAS - Free Stain Resistance

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	500,000 DR
Colorfastness to Crocking	Wet: 3 Dry: 4
Breaking Strength	Fill: 460 Warp: 388
Tear Strength	Fill: 52 Warp: 42
Colorfastness to Light	200 Hours
Cleaning Code	WS
Brush Pill	Class 4

CLEANING INSTRUCTIONS

Prompt cleaning is always recommended. Ordinary dirt and stains can be removed with a mild soap and water. Rinse the cleaned area with clean water and dry with a lint-free cloth. Connect will resist, without serious discoloration, the repeated actions of normal dilutions of non-abrasive chlorine or ammonia-based cleaners.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead / Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

PFAS Free

*Prop 65 Compliant

*CAB2998 Compliant

RECOMMENDED APPLICATIONS



KEYSTONBROS.COM | KBCONTRACT.COM

5/2025