



HENDRIX

GENERAL SPECIFICATIONS

Width 56.5"

14.976 oz / linear yard Weight

Surface: 100% Polyester Composition

Backing: Light Acrylic

Direction Railroaded

7.250" H x 7.188" V Repeat

Finish PFAS - Free Stain Resistance

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013 Passes

> NFPA 260 Passes

UFAC Class 1 Passes

PERFORMANCE SPECIFICATIONS

Abrasion 63,000 DR

Colorfastness Wet: 3 to Crocking Dry: 4

Seam Slippage Fill: 50

Warp: 52

Tear Strength Fill: 16

Warp: 7

Colorfastness to Light Class 4 at 40 hours

Cleaning Code WS, BC

> Brush Pill Class 3

Bleach Cleanable Yes - 10% Dilution

RECOMMENDED APPLICATIONS









HOSPITALITY RESTAURANT WORKSPACE SENIOR LIVING

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned. BC - Lightly spray with a 10% dilution of household bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead / Heavy metal free


BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

PFAS Free

*Prop 65 Compliant

*CAB2998 Compliant



HENDRIX REPEAT









*ACT® Registered Certification Marks