



PLUSH

GENERAL SPECIFICATIONS

| | |
|---------------------------------|--|
| Width | Approx. 57.5" |
| Weight | 14.96 oz / linear yard |
| Composition | Surface: 70.35% Polyester (UV), 29.65% Seaqual UV Polyester Backing: Light Acrylic Backing |
| Railroaded | No |
| Finish | PFAS - Free Stain Resistance |
| Minimum Yardage Custom Color | 300 Yards |

FLAME RETARDANCY SPECIFICATIONS

| | |
|-----------------|--------|
| CAL-TB 117-2013 | Passes |
| NFPA 260 | Passes |
| UFAC Class 1 | Passes |

PERFORMANCE SPECIFICATIONS

| | |
|------------------------------|------------------------|
| Abrasion | 63,000 DR |
| Colorfastness to Crocking | Wet: 3 Dry: 4 |
| Seam Slippage | Fill: 120 Warp: 102 |
| Tear Strength | Fill: 11 Warp: 12 |
| Colorfastness to Light | 1,200 Hours |
| Cleaning Code | WS, BC |
| Brush Pill | Class 4 |
| Bleach Cleanable | Yes - 10% Dilution |

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned. BC - Lightly spray with a 10% dilution of household bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead / Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

PFAS Free

*Prop 65 Compliant

*CAB2998 Compliant



*ACT® Registered Certification Marks

RECOMMENDED APPLICATIONS



HOSPITALITY



RESTAURANT



WORKSPACE



SENIOR LIVING



OUTDOOR

