



AVENUE

GENERAL SPECIFICATIONS

Width	54"
Weight	35 oz/linear yard
Roll Size	30 yds
Thickness	1.2 mm
Composition	100% PVC – Phthalate Free
Backing	75% Polyester, 25% Cotton

PERFORMANCE SPECIFICATIONS

Abrasion	200,000+ DR
Colorfastness to Crocking	Dry: 4.5 Wet: 4.5
Cold Crack	-20°
UV Resistance	200 Hours
Sulfide Stain Resistant	Yes
CAB 2998 Compliant	Yes

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
FMVSS 302	Passes
ASTM E84 Class 1	Passes
UFAC Class 1	Passes
BIFMA	Passes
IMO 2010 FTP	Passes

FINISHES



RECOMMENDED APPLICATIONS



WORKSPACE



HOSPITALITY



RESTAURANT



SENIOR LIVING

CLEANING INSTRUCTIONS

Prompt cleaning is always recommended. Ordinary dirt and stains can be removed with mild soap and water. Rinse the cleaned area with clean water and dry with a lint-free cloth. Avenue will resist, without serious discoloration, the repeated actions of normal dilutions of non-abrasive chlorine or ammonia-based cleaners.



*ACT® Registered Certification Marks