

# ELIOT

#### PERFORMANCE SPECIFICATIONS

		Abrasion	100,000+ DR
GENERAL SPECIFICATIONS Width 54"		Colorfastness to Crocking	Wet: 4.5 Dry: 5
		Seam Slippage	Fill: 73.5 Warp: 78.5
Weight	54 18-19 oz/linear yard	Tensile Strength	Fill: 129 Warp: 273.2
Surface Composition	95% High Solid Polyurethane (Polycarbonate), 5% Silicone	Colorfastness to Light	Class 4 at 40 Hours
		Cleaning Code	SW
Substrate Composition	100% Polyester	Stain Resistant	Yes
		Brush Pill	Class 5
Gauge	0.040	Hydrolysis Resistance	15 weeks
Thickness	1.00 mm	Anti-Bacterial	Passes
		Anti-Microbial	Passes
FLAME RETARDANCY SPECIFICATIONS		Bleach Resistant	Yes – 20% Dilution
CAL-TB 117-2013	Passes	Stain Resistant	Yes
NFPA 260	Passes	Denim Dye Resistant	Yes
	rasses	Ink Resistant	Yes
UFAC Class 1	Passes	Sulfide Stain Resistant	Yes

### REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop  $\mathbf{65}$ 

#### Phthalate Free

Lead Free

BPA Free/TRIS Free/Formaldehyde Free

Does not contain Conflict Minerals

Does not contain Flame Retardant Chemicals

Does not contain Anti-Microbial/Anti-Bacterial Chemicals

PVC Free

#### RECOMMENDED APPLICATIONS





▲☆ ♥ 業 ↔\* \*ACT® Registered Certification Marks

## FINISHES

