



SILVERTEX

GENERAL SPECIFICATIONS

Width	54"
Weight	30 oz/linear yard
Roll Size	30 yards
Composition	Vinyl / Urethane Topcoat
Backing	100% Polyester Ultra Hi-Loft ² ™

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	100,000 DR
Cold Crack	-10°
UV Resistance	1,000 Hours
CAB 2998 Compliant	Yes

FINISHES

PERMABLOK®
ADVANCED VINYL PROTECTION

CLEANING INSTRUCTIONS

Get rid of stains with one of the following steps:	
Step 1	eye shadow, mascara, grease, black felt tip pen, crayon, chocolate, suntan lotion, and hair/body oils*
Step 2	red lipstick
Step 3	blood, urine, feces, oil base paint, tar and asphalt
Step 4	all other tough stains

Step 1: Remove excess spill with a damp cloth. Clean with a 1:1 mix of Ivory® liquid soap and water. Next, rinse with clean water and dry.

Step 2: Use a straight application of concentrated cleaners such as Formula 409® or Fantastik® spray cleaner. Wipe with a clean cloth, rinse with water and dry.

Step 3: Use a 1:1 mix of ammonia and water, or a 1:10 mix of bleach and water. Rinse with clean water and dry.

Step 4: Use a 1:1 mix of isopropyl alcohol and water. If the stain persists, use straight alcohol. Rinse thoroughly with clean water and pat dry.

Note: For cleaning that requires step 4, use a soft cotton cloth saturated with the cleaning material and rub the stain in circles 10 times. Pat dry with another soft cotton cloth and check the results. *Must be cleaned after each instance of exposure to hair and body oils.

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks