



# TWIST

## GENERAL SPECIFICATIONS

Width	54"
Weight	30 oz/linear yard
Roll Size	30 yards
Composition	100% PVC (Phthalate Free)
Backing	100% Polyester

## FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

## PERFORMANCE SPECIFICATIONS

Abrasion	250,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Cold Crack	-20°
Colorfastness to Light	300 Hours
Sulfide Stain Resistant	Yes
Bleach Cleanable	10% dilution
CAB 2998 Compliant	Yes

## CLEANING INSTRUCTIONS

Prompt cleaning is always recommended. Ordinary dirt and stains can be removed with mild soap and water. Rinse the cleaned area with clean water and dry with a lint-free cloth. Twist will resist, without serious discoloration, the repeated actions of normal dilutions of non-abrasive chlorine or ammonia-based cleaners.

## RECOMMENDED APPLICATIONS



WORKSPACE



EDUCATION



HEALTHCARE



HOSPITALITY



RESTAURANT



SENIOR LIVING



\*ACT® Registered Certification Marks

## FINISHES

