



WEAVER

GENERAL SPECIFICATIONS

Width	54"
Weight	11-12 oz/linear yard
Composition	100% Polyester
Backing	SBR

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Light	40 Hours
Colorfastness to Crocking	Wet: 5 Dry: 5
Breaking Strength	Fill: 139 Warp: 330
Seam Slippage	Fill: 36 Warp: 81.5
Tear Strength	Fill: 40.3 Warp: 61.5
Brush Pill	Class 4.5 per ASTM D3511
Cleaning Code	SW - Solvent or Spot Clean

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Pretest a small, inconspicuous area before proceeding. Do not saturate. Pile fabrics may require brushing with a non-metallic, stiff bristle brush to restore appearance. Hot water extraction or steam cleaning is not recommended. Cushion casings should not be removed and laundered or dry cleaned separately. To prevent overall soiling, frequent vacuuming or light brushing with a non-metallic, stiff bristle brush to remove dust and grime is recommended. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling. Use a professional furniture cleaning service when an overall soiled condition has been reached.

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

