



WOOLF

GENERAL SPECIFICATIONS

Width	54"
Weight	18-19 oz/linear yard
Surface Composition	95% Polyurethane (Polycarbonate), 5% Silicone
Substrate Composition	100% Polyester
Gauge	0.040
Thickness	1.00 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

Phthalate Free

Lead Free/Heavy Metal Free

BPA Free/TRIS Free/Formaldehyde Free

Does not contain Conflict Minerals

Does not contain Flame Retardant Chemicals

Does not contain Anti-Microbial/Anti-Bacterial Chemicals

PVC Free

CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	300,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 65.3 Warp: 67.08
Tensile Strength	Fill: 126 Warp: 182
Tear Strength: Tongue Tear	Fill: 15 Warp: 11
Hydrolysis Resistant	15 weeks
Anti-Bacterial, Anti-Microbial, Mildew Resistant, Denim Dye Resistant	Passes
Cold Crack	-20° F
Colorfastness to Light	200 Hours
Bleach Resistant	Yes - 20% Dilution

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

