

SPECKLE

GENERAL SPECIFICATIONS

Width	54"
Weight	24.5 oz / linear yard
Composition	88% Polyester, 7% Acrylic, 3% Polyurethane, 2% Silicone
Backing	100% Polyurethane
Finish	Supreen™ Stain and Moisture Barrier
Minimum Yardage	500 Yards
Custom Color	

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 5.0 Dry: 4.5
Seam Slippage	Fill: 124 Warp: 113
Tear Strength	Fill: 28.5 Warp: 28.2
Colorfastness to Light	Class 5
Brush Pill	Class 4.5
Cleaning Code	SW - Solvent or Spot Clean
Bleach Cleanable	Yes - 10% Dilution

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned. BC - Lightly Spray with a 10% dilution of household bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead / Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

PFAS Free

*Prop 65 Compliant
*CAB2998 Compliant

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

